



DATA SHEET MINERAL FIBRE

Product	OWA 20mm Sinfonia
ASTM E 1264 Classification	Type IV, Form 2, Pattern E
Material	bio-soluble mineral wool, free of asbestos and produced without formaldehyde 100 % recyclable
Reaction to fire	A2-s1,d0 (EN 13501-1) class 1 (ASTM E84) class A (ASTM E 1264)
Light reflection	approx. 87 (ISO 7724-2, ISO 7724-3)
Thickness	nom. 20 mm
Edge	SQUARE EDGE (SQ) SHADOWLINE TEGULAR (SLT)
Dimensions	600 x 600 x 20mm, 1200 x 600 x 20mm
Sound absorption	NRC = 0.80 according to ASTM C423
Sound reduction*	CAC = 35 - 39* according to ASTM E1414
Humidity resistance	up to 95 % RH
Scrubbability and Washability	Tested according to ASTM D2486 and D4828
Mold Resistance	according to ASTM D3273
VOC and Formaldehyde Emissions	compliant with CDPH Standard Method v1.1
Clean room class	ISO 5 (ISO 14644-1)
Total Recycle Content	32 % (14 % pre-consumer and 18 % post-consumer)
Coeff. of Thermal Conductivity	0.055 W/mK
Environmental Protection	ISO 14001-2003

 $^{^{\}star}$ CAC range is based on plenum space and other factors as mentioned in the OWA CAC data sheet.



^{*} dependent on system, soffit and other project specific factors